

## MSE600

### Model: MSE-600 Series Magstripe Card Encoder (Low-Co. only)

MSE-600 W(P)Series

Magstripe Card & Passbook Encoder



- Compatible with ISO 7811/2, 7811/4, 7811/5 for reading and encoding data in track 1, track 2, track 3 that exist in magnetic stripe.
- Provide RS-232 interface to host.
- Built-in high level serial interface commands set.
- Bundled with one software demo-package.
- Passbook encoder/reader is available.

### Specifications

#### CARD WRITER/READER

Power	+ 12VDC±10%, Read: 250mA (Typ.), 370mA (Max) Write: 750mA (Max.) Write Triple Track: 690mA Write Dual Track: 550mA Write Single Track: 420mA
Output	Baud Rate 9600, 8 bit Character, Non-Parity
Dimensions	200mm (L) x 55.5mm (H) x 59mm (W)
Cable	5 Ft (1.5m)
Connector	DB-9 Female
Card Density	encoding/Decoding : 75~210 BPI
Configurations	Single Track : Track 1,2 or 3, JIS-II Dual Track : Track 1&2 or 2&3 Tripe Track : Track 1&2&3
Encoding Energy	300 Oersted
Recording Capability	Track 1 (TATA) : 79 characters Track 2 (ABA) : 40 characters Track 3 (THRIFT) : 107 characters JIS-II : 69 characters

א.נ. יעף - טכנולוגיות איסוף נתונים בע"מ

רח' נשיאי ישראל 5, רמת גן 52247 טלפון: 03-5748680 08-9389325 פקס: 03-5748681

[www.yaaf.co.il](http://www.yaaf.co.il)

E-MAIL: [mail@yaaf.co.il](mailto:mail@yaaf.co.il)