

QuickScan[®] QS6000 Plus

Handheld Scanner



Ideal for:

- All in-store applications

Features:

- Low power consumption
- AutoSense[®] stand for hands-free operation
- Dual interfaces with AutoSelect[™]
- Optional EAS antenna for simultaneous scanning and security tag deactivation
- Universal wedge for additional keyboard emulation, bar code symbologies and data editing

Checkout The Handheld Scanner That Is Setting The New Standard At Retail Checkout Around The World

Great Performance is now even Better!

The QuickScan[®] QS6000 Plus handheld scanner offers great performance at a very affordable price. With a high first pass read rate and the best speed-to-read of any scanner in its class, the QS6000 Plus speeds retail checkout. And its 33 cm / 13" depth-of-field with 100% UPC labels extends the user's working range.

With a high visibility option, utilizing a 650nm laser diode, the user can target and read bar codes even in bright light conditions due to the scanner's inherent tolerance of high ambient light conditions. Plus, PSC's advanced electronics perform well even when reading low contrast labels with poor edge definition.

Hardened for Tough Store Environments

The QS6000 Plus scanner incorporates the most advanced, high durability features available today. The reading engine and optics are protected by anti-shock mounts built to absorb up to 1500 Gs. In fact, the QS6000 Plus can withstand repeated five-foot drops to concrete.

The QS6000 Plus also features a strong, plastic enclosure that guards against liquid and dust infiltration. A tough, rubber-like shield cushions the scanner when dropped, protects the scan window from scratching and prevents the scanner from slipping off counter surfaces.

Lightweight & Ergonomic For Maximum Scanning Comfort & Productivity

The QS6000 Plus scanner was developed with operator comfort in mind—a critical factor that ensures prolonged operator productivity. The weight of its evenly balanced design can be held easily in any size hand, even during extended periods of use. When resting on a horizontal surface, in a stand, or in a belt holster, the handle is quickly and easily grasped for "scoop and scan" simplicity.

The QuickScan[®] QS6000 Plus: An Outstanding Value

With the QS6000 Plus scanner, there's no need to make trade-offs between quality and affordability. High-end performance, advanced ergonomic design, enhanced durability—the combination of these features in the QS6000 Plus adds up to one of the best values in the industry.



Specifications

QS6000 Plus

These product Specifications are subject to change without notice. Additional information concerning this product or other PSC products and services can be found at the PSC website: www.pscnet.com or contact your PSC representative for more information.

Specifications apply to RS232 interface with 680nm VLD unless otherwise stated.

Mechanical

Dimensions: 16.51 x 7.01 x 10.74 cm / 6.50 x 2.76 x 4.23"

Weight

Scanner: 170 g / 6.0 ozs.
Cable (81 cm/32"): 176 g / 6.2 ozs.

Cable length options

Collapsed: 81 cm / 32",
Max. Working: 183 cm / 72";
Collapsed: 203 cm / 80",
Max. Working: 305 cm / 120"

(For other cable options, contact your PSC sales representative.)

Optical

Light source: Visible Laser Diode(VLD), 680 nm-nominal (650 nm-optionnel)

Scan system: Electromagnetic dithering mirror

Rate: 42 scans/sec. (nominal)

Depth-of-field: Refer to chart on this page

Resolution: 0.13mm / 5 mils

Print contrast ratio: 30% minimum

Pitch: ±65°

Skew: ±55°

Scan angle: 46°

Ambient light immunity

Artificial light: 12600 Lux / 1,200 foot candles

Sunlight: 84000 Lux / 8,000 foot candles

Electrical

NOTE: Specifications using the 680 nm laser diode & cable

Operating voltage

Undecoded: 4.2 V to 14 VDC
Decoded: 4.5 V to 14 VDC

Operating current - nominal

Undecoded: 70 mA to 5 VDC
Decoded: 120 mA to 5 VDC

Idling current - nominal

Undecoded: 10 µA to 5 VDC,
Decoded: 23 mA to 5 VDC;
Decoded, lowest power mode: 14 mA to 5 VDC

Environmental

Temperature

Operating: 0° to 50° C / 32° to 122° F
Storage: -40° to 70° C / -40° to 158° F

Humidity:

5 to 95% NC
Shock (at 23°C): Withstands multiple 1.5 m / 5.0' drops onto concrete / 100+ drops to countertop

Vibration:

MIL-STD-810E
Water & Dust: Resistant, IEC529 rating IP53DW

Decoding Capability

- UPC A, E / EAN 8,13 / JAN 8,13 (Codes add-ons P2 / P5, Code 128)
- Code 128/EAN 128
- Codabar
- Pharmacode 39
- Code 93
- Interleaved 2/5
- Standard 2/5, IATA
- Code 39
- MSI/Plessey

Communications

AutoSelect™ cable determines active interface

- IBM 4682/92 (Port E)
- IBM 4683/84 (Ports 5B & 9B) and Wand Emulation
- IBM 4693/94 (Ports 5B & 9B) and Wand Emulation
- IBM 46XX / USB Embedded with USB Single Cable
- RS232 & IBM 46xx
- RS232 & Wand Emulation
- RS232 & Standard Keyboard Wedge
- OCIA (formats SP & NCR) & RS232
- Standard Keyboard Wedge & Wand Emulation
- Universal Keyboard Wedge
- Undecoded

Safety & Regulatory

Electrical: Complies to: Gost R; TÜV; UL; cUL

Emissions: Complies to: FCC-A; EN 55022-B;

BCIQ CNS 13438; AS/NZS 3548; VCCI-B

Laser classification: CDRH Class IIa ;

(ATTENTION: Laser Radiation - do not stare into beam); IEC 60825 Class 1 & 2



Depth-of-Field		
Printing resolution, contrast and ambient light dependent		
Label Density	Range	
5 mils	2.5 to 7.6 cm	1.0 to 3.0"
7.5 mils	1.3 to 15.2 cm	0.5 to 6.0"
10 mils	0.0 to 22.9 cm	0.0 to 9.0"
13 mils	0.0 to 33.0 cm	0.0 to 13.0"
20mils	up to 48.3 cm	up to 20.0"

Available Mount Options



P/N: 7-0204
AutoSense®

P/N: 7-0470
AutoSense®
(w/o base)

P/N: 5-0788
Universal Holster

P/N: 7-0393
Mountable
Tabletop

PSC Inc.

959 Terry Street
Eugene OR 97402-9150 USA
Tel: 800 695 5700 or 541 683 5700
Fax: 541 345 7140

PSC Worldwide Sales and Service locations

European Headquarters
Europe/Middle East/Africa
PSC Bar Code Limited
Axis 3, Rhodes Way
Watford, England WD24 4TR
Tel: 44 1923 809500
Fax: 44 1923 809505

Belgium
Tel: 32 2 414 74 09
Fax: 32 2 410 11 63
Sweden
Tel: 46 4010 84 92
Fax: 46 4010 84 91

France
Tel: 33 1 64 86 71 00
Fax: 33 1 64 46 72 44
Turkey
Tel: 90 212 236 91 15
Fax: 90 212 236 91 16

Germany
Tel: 49 6151 93580
Fax: 49 6151 935858

Italy
Tel: 39 0 39 629031
Fax: 39 0 39 6859496

Spain
Tel: 34 91 203 65 00
Fax: 34 91 203 65 01

Asia Pacific Headquarters
PSC Hong Kong
12 Harcourt Road
Bank of America Tower 8th Floor
Hong Kong
Tel: 852 2 584 6210
Fax: 852 2 521 0291

Australian Headquarters
PSC Asia Pacific Pty Ltd
Unit 11
277 Lane Cove Road
North Ryde NSW 2113
Tel: 61 2 9878 8999
Fax: 61 2 9878 8688

Japanese Headquarters
PSC Japan KK
9F Gotanda Daiwa Bldg.
7-13-5 Nishigotanda
Shinagawa-Ku, Tokyo 141-0031
Tel: 81 3 3491 6761
Fax: 81 3 3491 6656

Latin American Headquarters
PSC Latin America
1110 Brickell Avenue
Suite 505
Miami FL 33131 USA
Tel: 1 305 539-0111
Fax: 1 305 539-0206



This product is manufactured in the United States and Singapore.